
INFRATUBETM



MEDIUM WAVE INDUSTRIAL INFRARED HEATERS



W-SERIESUp to 4000 watts / 13684 btu's Single Element

Infratech W-series Heaters are versatile electric infrared units for industrial applications. The fixtures can be used on open frames or in grated into existing oven enclosures.

Electric infrared curing enhances manufacturing processes and typically improves finish quality and adhesion. Electric infrared curing works well withvirtually all air dry coatings including; primers, sealers, base coats, stains, varnishes, clear coats, adhesives, and top coats.

The Infratube fixtures are compact and energy efficient with a curved parabolic reflector to uniformly distribute heat. These fixtures are reliable with no moving parts and long lasting tubular quartz infrared heating elements.

Infratube fixtures are easy to install and have a variety of mounting options that include flush mount frames and surface mount brackets.

All Infratech units are UL Listed and are available with a wide variety of ULListed control options. One year manufacturers warranty on all equipment.

FLUSH MOUNTING FRAME






Infratech Infratube fixtures are commonly used in many applications including:

- Woodworking
- Laminating
- Web Processing
- Shrink Wrap
- Pre Heating
- Plastic Forming
- Drv Off
- Spot Curing
- Powder Coating
- Automotive Refinishing

Many different controls are available

State of the art digital, solid state, and analog controls. Up to 50 amps. Many options available, including multiple zones, timers and non-contact infrared thermocouples.









INFRATUBE™

INFRARED RADIANT HEATERS ITEM LIST

POW	DER COATED FIXTURES (BEIGE)						
Part No.	DESC.	Length	BTU'S	Watts	Volts	Amps	Ship Wt.
22-1040	W-1512 FIXTURE	33"	5,118	1500	120V	12.5	12
22-1045	W-1524 FIXTURE	33"	5,118	1500	240V	6.3	12
22-1055	W-2024 FIXTURE	39"	6,824	2000	240V	8.4	13
22-1100	W-3024 FIXTURE	61-1/4"	10,236	3000	240V	12.5	20
22-1125	W-4024 FIXTURE	61-1/4"	13,648	4000	240V	16.7	20
DUAL	ELEMENT POWDER COATED FIXTURES	(BEIGE)					
Part No	DESC.	Length	BTU'S	Watts	Volts	Amps	Ship Wt
22-2100	WD-4024 FIXTURE	39"	13,648	4000	240V	16.7	
22-2200	WD-5024 FIXTURE	39"	17,060	5000	240V	20.8	-
22-2300	WD-6024 FIXTURE	61-1/4"	20,472	6000	240V	25	
22-2400	WD-8024 FIXTURE	61-1/4"	27,296	8000	240V	33.4	795.7
22-2400	WD-0024TIATORE	01-17-	27,200	0000	2407	00.4	
	NLESS STEEL FIXTURES		57.00				la
Part No.	DESC.	Length	BTU'S	Watts	Volts	Amps	Ship Wt.
21-1040	W-1512-SS FIXTURE	33"	5,118	1500	120V	12.5	
21-1045	W-1524-SS FIXTURE	33"	5,118	1500	240V	6.3	
21-1055	W-2024-SS FIXTURE	39"	6,824	2000	240V	8.4	
21-1100	W-3024 SS FIXTURE	61-1/4"	10,236	3000	240V	12.5	
21-1125	W-4024-SS FIXTURE	61-1/4"	13,648	4000	240V	16.7	20
DUAL	ELEMENT STAINLESS STEEL FIXTURES	S					
Part No	DESC.	Length	BTU'S	Watts	Volts	Amps	Ship Wt.
21-2100	WD-4024 FIXTURE	39"	13,648	4000	240V	16.7	14
21-2200	WD-5024 FIXTURE	39"	17,060	5000	240V	20.8	14
21-2300	WD-6024 FIXTURE	61-1/4"	20,472	6000	240V	25	22
21-2400	WD-8024 FIXTURE	61-1/4"	27,296	8000	240V	33.4	22
	ALL ABOVE FIXTURES CAN BE SP	ECIAL ORDE	RED WITH 208	3 VOLTS, 277	VOLTS, OR 48	OVOLTS	
14-4092	INF-10 120V INPUT REGULATOR w/KNOB			1500	120	2	1
14-4094	INF-20 240V INPUT REGULATOR w/KNOB			3000	240	2	1
CONT	TROLS						
Part No	0.000 (a) = 0.000 (a) = 0.000 (b) = 0.000	Description					Ship Wt.
30-4000	50 AMP	50 Amp 1 Zone Intensity Control Analog					25
30-4005	A STATE OF THE STA	Digital 50 Amp 1 Zone Intensity Control					45
30-4010	and Vallot Vallo	Digital 1 Zone Control w/Timer					45
30-4015	TARREST AND	IR Thermocouple Control SENSOR NOT INCLUDED					45
30-4020	THE WAS INDEED.	IR Thermocouple Control w/Timer SENSOR NOT INCLUDED					45
30-4025		Digital 3 Zone Control					45
30-4030	00000	Digital 3 Zone Control w/Timer					45
	DTOC-200 CONTROL 240V / 480V	SEPARATE OVEN AND SPRAYBOOTH 200 AMPS					75
	SC-200 CONTROL 240V / 480V	COMBINATION OVEN AND SPRAYBOOTH 200 AMPS					3
	OC-200 CONTROL-240V / 480V	OVEN ONLY 200 AMPS				1	
	ADD FOR MAIN DISCONNECT	200 AMP MAXIMUM					
	ADD FOR ADDITIONAL HEAT ZONE						
		ON / OFF CONTROL ONLY					
	ADD FOR IR / TC CONTROLLER	PROBE OR SENSOR NOT INCLUDED					
	LADD FOR TIC BROSE	BY QUOTE ONLY					
X-30-1140	ADD FOR T/C PROBE			-11-2-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1		12	
X-30-1140 X-30-1150	ADD FOR T/C PROBE ADD FOR IR SENSOR CUSTOM CHAIN SUSPENDED SYSTEM		BY QUO	TE ONLY		2- 	

